

Northfield Corporation

O.E.M. OF NORTHFIELD CONTINUOUS FEED COUPON INSERTERS





Featuring:

- · Complete parts inventory on all equipment
- Service technicians available 24 hours a day, 7 days a week.
- Over 25 years experience worldwide with numerous companies, both large and small
- In-field consultation

Dedicated to efficient installation, service, and sales of pressure sensitive labelers, coupon inserting equipment, and neck hanger/ElastiTag® applicators which ensures that the correct equipment is used for every job, every time.

Northfield 1600SRV Inserter

Continuous Feed Inserter Specifications:

Power Requirements: 115/230 VAC filtered, 50-60 cycles,

5 amps.

Max Speed: Up to 400+ pieces per minute


*Dependent on insert size and product

Linear Speed, In-Feed: Up to 6,000 I.P.M. Linear Speed, Out-Feed: Up to 6,000 I.P.M.

Controls: Applied Motion Products, Maple Systems

Controller Dimension: 16" High, 14" Wide, 6" Deep

Head Weight: 25 lbs.
Controller Weight: 34 lbs.
Lubrication Needs: None
Change Parts: None
Air Requirements: None



Minimum Insert Size: 1" Wide x 1" Long
Maximum Insert Size: 6" Wide x 7" Long
Insert Thickness: Up to 1/16"

Splices: Heat Seal Factory Splices Only


Burst Tensile Strength: 8-12 lbs. Recommended not to


exceed 17 lbs.


The Northfield Model 1600SRV 2D inserter is capable of accurately inserting 2D overwrapped, NX2Food, and perforated paper inserts; either in roll or bandoiler form. Some of the application examples are: horizonal/vertical fillers, carton lines, open container lines, and hot melt on/in pack applications.

Insert examples: game pieces, sweepstakes, coupons, instructions, rebates, etc.

Dimensions, Head







Distributed by:

NORTHFIELD CORPORATION

1870 Commerce Drive • De Pere, WI 54115 920-983-8122 • Fax 920-983-8124

www.northfieldcorp.com